

24-547950081/547950121/547950201/547950085 114  
BUS No.: 15805

REVISION DATE: April 2007



### SAFETY DATA SHEET SEALOMIX (SEALCRETE)

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME SEALOMIX (SEALCRETE)  
 PRODUCT NO. 180420, 185425, 185402, 185449, 185463, 185470  
 SUPPLIER BOSTIK LIMITED  
 COMMON ROAD  
 STAFFORD  
 STAFFORDSHIRE ST16 3EH  
 +44 1785 255141  
 +44 1785 272650  
 EMERGENCY TELEPHONE +44 1785 255141 +44 1785 272650

#### 2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
ROSIN	232-475-7	8050-09-7	1-5%	R43
SODIUM HYDROXIDE	215-185-5	1310-73-2	< 1%	C,R35

The Full Text for all R-Phrases are Displayed in Section 16

#### 3 HAZARDS IDENTIFICATION

May cause sensitisation by skin contact.

CLASSIFICATION R43.

#### 4 FIRST-AID MEASURES

##### INHALATION

Remove victim immediately from source of exposure. Move the exposed person to fresh air at once. Get medical attention.

##### INGESTION

DO NOT induce vomiting. Get medical attention immediately.

##### SKIN CONTACT

Remove affected person from source of contamination. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

##### EYE CONTACT

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get medical attention.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

##### SPECIFIC HAZARDS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

#### 6 ACCIDENTAL RELEASE MEASURES

##### PERSONAL PRECAUTIONS

Avoid skin and eye contact. Wear personal protective equipment. Avoid breathing vapour. Ensure adequate ventilation.

##### ENVIRONMENTAL PRECAUTIONS

Prevent entry into drains and water courses.

## SEALOMIX (SEALCRETE)

### SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Wash thoroughly after dealing with a spillage. Do not seal drum immediately (evolution of carbon dioxide), allow to ventilate for several days before sealing.

### 7 HANDLING AND STORAGE

#### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Provide good ventilation. Persons susceptible for allergic reactions should not handle this product.

#### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

#### STORAGE CLASS

Chemical storage.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
SODIUM HYDROXIDE	WEL				2 mg/m3

#### INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

#### PROTECTIVE EQUIPMENT



#### ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

#### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit. Wear mask supplied with: Gas cartridge suitable for organic substances.

#### HAND PROTECTION

Use protective gloves made of: Nitrile. Use thin cotton gloves inside the rubber gloves if allergy risk.

#### EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

#### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear long-sleeved clothing.

#### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

### 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	Red brown
SOLUBILITY	Soluble in water
RELATIVE DENSITY	1.015

### 10 STABILITY AND REACTIVITY

#### STABILITY

Stable under normal temperature conditions.

#### CONDITIONS TO AVOID

Avoid contact with strong oxidisers.

**SEALOMIX (SEALCRETE)****HAZARDOUS DECOMPOSITION PRODUCTS**Fire or high temperatures create: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).**11 TOXICOLOGICAL INFORMATION****INHALATION**

May cause sensitisation by inhalation. May cause respiratory allergy.

**INGESTION**

May cause discomfort if swallowed.

**SKIN CONTACT**

May cause sensitisation by skin contact. May cause skin irritation/eczema.

**EYE CONTACT**

May cause severe irritation to eyes.

**MEDICAL CONSIDERATIONS**

Skin disorders and allergies. History of smoking. Chronic respiratory and obstructive airway diseases.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

Not regarded as dangerous for the environment. However, contamination of the aquatic or terrestrial environments should be avoided.

**13 DISPOSAL CONSIDERATIONS****DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION****GENERAL**

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

**MARINE POLLUTANT**

No.

**15 REGULATORY INFORMATION****LABELLING**

Irritant

**CONTAINS**

ROSIN

**RISK PHRASES**

R43

May cause sensitisation by skin contact.

**SAFETY PHRASES**

S24

Avoid contact with skin.

S37

Wear suitable gloves.

S46

If swallowed, seek medical advice immediately and show this container or label.

S56

Dispose of this material and its container to hazardous or special waste collection point.

S2

Keep out of the reach of children.

**APPROVED CODE OF PRACTICE**

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

**GUIDANCE NOTES**

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

**16 OTHER INFORMATION**

## SEALOMIX (SEALCRETE)

### GENERAL INFORMATION

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services.

### INFORMATION SOURCES

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

### REVISION COMMENTS

This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Limited.

### ISSUED BY

Approved ID

REVISION DATE April 2007

REV. NO./REPL. SDS GENERATED 2

DATE Sept 2006

### RISK PHRASES IN FULL

R35 Causes severe burns.

R43 May cause sensitisation by skin contact.